
Storage Ring X-ray Beam Position Monitor Development

Glenn Decker, Om Singh

- XFD / ASD X-ray beam stability task force (XAXSTF) results
- X-ray BPM based orbit control


Argonne National Laboratory Advanced Photon Source APS Diagnostics







X-ray BPMs (16, 20 meters from source)



Focusing Quadrupole Magnet

Defocusing Quadrupole Magnet


Sextupole Magnet

Combined Function Horz./ Vert. Steering Corrector Magnet

Argonne National Laboratory Advanced Photon Source APS Diagnostics



Concept for Reduction of ID X-bpm Stray Radiation Background Signals



Stray radiation from downstream AM dipole, quadrupoles, sextupoles and

Argonne National Laboratory Advanced Photon Source APS Diagnostics




Ray Tracing Analysis for Girder Realignment Upstream Dipole X-radiation Fan Insertion Device X-rays **Before Modification** After Modification Downstream Dipole X-radiation Fan **Charged Particle Beam Trajectory Argonne National Laboratory** Univ. of Chicago Review Advanced Photon **Advanced Photon Source** Glenn Decker

Source


September 30, 1999

APS Diagnostics






Variation of Insertion Device Beamline Blade Voltages with Downstream Dipole Steering



Argonne National Laboratory
Advanced Photon Source
APS Diagnostics



Variation of Insertion Device Beamline Blade Voltages with Upstream Dipole Steering




Advanced Photon Source APS Diagnostics



Glenn Decker September 30, 1999

Variation of Insertion Device Beamline Blade Voltages with ID Steering (Open Gap)




APS Diagnostics



September 30, 1999


Variation of Insertion Device Beamline Blade Voltages with ID Steering (Open Gap)




Advanced Photon Source **APS Diagnostics**



Glenn Decker **September 30, 1999**







Advanced Photon Source APS Diagnostics




Glenn Decker September 30, 1999

XAXSTF Summary

- Realignment of accelerator girders was performed at 34-ID during the 12/98 accelerator maintenance period with no negative impact on accelerator operation.
- This technique was shown to be effective in reducing the contribution of stray radiation to insertion device X-ray beam position monitor blade signals by up to a factor of ten.
- Research is ongoing to determine justification / need for performing realignment for operational beamlines.




Storage Ring Bpms



Argonne National Laboratory Advanced Photon Source APS Diagnostics



Storage Ring Vertical Correctors





- Two columns of correctors (A2/B3) are used for global controls
- Three additional correctors are added for BM14 local controls
- Two additional correctors are added for ID17 local control

Argonne National Laboratory Advanced Photon Source APS Diagnostics



BM14 Xbpm Feedback Results for an Operational Run







Advanced Photon Source APS Diagnostics



Om Singh September 30, 1999









X-bpm based Orbit Control -- Summary

- XBPM electronics upgrade and software modifications have been made in BM14 and ID17 beamline, such that the XBPM orbit control is integrated into the existing operational RFBPM based DC orbit control.
- Results from bending magnet (BM14) XBPM feedback during operational runs have shown that fill to fill drift has been reduced by a factor of 6.
- The work on the insertion device beamline (ID17) is in progress to characterize and compensate for background radiation, before XBPM feedback wil be operational.
- Work is in progress to upgrade electronics for all bending magnet beamlines such that both DC and AC orbit feedback can be implemented. Work on the insertion device electronics upgrade will follow.

